h•teltime s•lutions





Content:

POS terminals	3
Printers	
Thermal and DMP printers	8
EPSON printers accessories	9
Accessories	10
Cash drawer, Decibar, other	

POS terminals

POS Terminal ELO 15E2

Features

Model: 15E2

Type: All-in-one (Monitor and PC in one)

Diagonal

measurement: 15,6" Resolution: 16:9

CPU: Celeron 2 GHZ, Quad-Core J1900

RAM: 4 GB

HDD: SSD 120 GB

USB: 4x 2.0
COM: 2x RS-232
LAN: 1x RJ45
VGA: VGA out
Audio: 1x 3,5mm

WIFI: No - USB adapter purchase required

OS: Windows POSReady 7

VESA Mount: Yes

Dimensions: 358x160x358mm

Weight: 5 kg





This All-in-one Point of Sale (POS) posseses an elegant designwhilst being very reasonably priced. It enables connection to older printers through COM and USB ports. Widescreen display resoltution (16:9) makes it ideal for use with our Vento App. Elo Touchsystem has maintained consistency of great quality POS products on the market for years. This termial is a market best seller with low propensity to malfunction.

POS Terminal ELO 15E3

Features

Model: 15E3

Typ: All-in-one (Monitor and PC in one)

Diagonal

measurement: 15" Resolution: 4:3

CPU: Celeron 2 GHZ, Quad-Core J1900

RAM: 4 GB

HDD: SSD 120 GB **USB:** 4x 2.0

COM: 2x RS-232
LAN: 1x RJ45
VGA: VGA out
Audio: 1x 3,5mm

WIFI: No - USB adapter purchase required

OS: Windows POSReady 7

VESA mount: Yes

Dimensions: 358x160x358mm

Weight: 5 kg





This cost effective All-in-one Point of Sale (POS) posseses an great design. It enables connection to older printers through COM and USB ports. It has a classic display resoltution (4:3). Elo Touchsystem has maintained consistency of great quality POS products on the market for years.

Portable POS devices Vento

Tablet iView Optimus C 8000

Features

Diagonal

measurement: 8"

CPU: Intel Z3735G Cherry Trail, Quad Core 1,83Ghz

 RAM:
 2 GB

 HDD:
 32 GB

 Audio:
 1x 3,5mm

 WIFI:
 Ano

OS: Windows 10

Battery life: up to 5 hours, 8000mAh

Weight: 419 g

Dimensions: 21 x 12,5 x 1,5 cm



This tablet is a much lighter version of larger POS terminal models. It's configuration is sufficient for portable POS device operations with optimal battery capacity 8000mAh. This is a very popular device for portable POS terminals.

Recommendation:

Pros: low price, slimmer design and low weight.

Cons: weaker WiFi (lower sensitivity)







Tablet Caterpillar T20

Features

Diagonal

measurement: 8", Gorilla®-glass

CPU: Intel Z8350 Quad Core 1.44GHz

RAM: 2 GB **HDD:** 64 GB **Audio:** 1x 3,5mm

WIFI: Yes **3G/4G/LTE**: Yes

OS: Windows 10

Battery life: Up to 6 hours, 7500 mAh

Weight: 650 g

Dimensions: 22 x 14,3 x 1,4 cm





This is another lighter version of larger POS terminal models. It's main advantage is rugged mechanical resiliance and increased dust and water resistance (IP67). It's configuration is sufficient for portable POS device with optimal battery capacity 7500mAh. We recommend this tablet for fast paced businesses.

Recommendation:

Pros: high quality factory production, increased dust and water resistance (IP67), anti-scratch display Gorilla Glass, drop proof up to 1.8 meters, long battery life

Cons: Slightly heavier

Tablet accesories

Tablet case for belt

Original hand made case with Vento logo can be purchased for 8 inch tablets listed in the brochure. The can be attached to a belt in multiple wayand it's internal part consists of fleece fabric, which allowes convenient mainenance of the display cleanliness.

Printers

Portable printers (for portable POS devices)

Star Micronics portable SM-L200-UB40

Type: Portable printer

Connection: Bluetooth

Battery Life: 13 hours (5 min print intervals)

Support: Windows
Paper width: 58 mm
Drop proof: 1.2m

Reliability: 50 km (37 mil. lines)

Dimensions: 8,3 x 12,2 x 4,4 cm


Weight: 220 g (with battery)

Features: LCD display

"Drop-In & Print" easy paper loading

Tear Bar

Desktop 5 volt "Drop-In & Charge" Cradle Option (not included in a package)



Optional accessories (not included):

- Horizontal desktop or vertical stand with belt strap
- Desktop Charging Cradle docking station

Star Micronics SM-L200 - Desktop Charging Cradle

Charging cradle for printer **SM-L200** desktop charging Input power is 5V.

Simple control "drop-in-and-charge".

Led light indicator lights up when printer is fully charged





Thermal and DMP printers

Epson TM-T20 II / USB / Dark grey

Printer type: thermal
Connection: USB
Paper width: 78mm
Logo print: Yes

Mode: ESC / POS

POS terminal printer Epson TM-T20 II posseses high quality and reliability. Printer connects by external adapter. Connection to PC is facilitated by USB (-B) cable.



Epson TM-T20 II / ETHERNET / Dark grey

Printer type: thermal

Connection: Ethernet (RJ 45, 10/100 Mb/s)

Paper width: 78mm Logo print: Yes

Mode: ESC / POS

This is the same printer type as it's USB version. It facilitates Ethernet to connect to a network. PC operation is not required in order for device to print. Stand-alone nature allows print of both checks or orders. Convenient installation through Epson Utility.



Star Micronics SP742 MC Printer, Black, paralel, cutter

Printer type: Dot matrix printing DMX

Connection: Ethernet (RJ 45, 10/100 Mb/s)

Paper width: 58 / 69,5 / 76 mm

Logo print: Yes

DMX printer is mostly used at locations, where thermal printing is not appropriate e.g. kitchen. Printer does not have USB port, it connects to network through Ethernet.



Printer CITIZEN CT-E351 black / white, Ethernet + USB, cutter

Printer type: thermal

Connection: Ethernet (RJ 45, 10/100 Mb/s) + USB2

Paper width: 78 mm Logo print: Yes

Mode: ESC / POS



New CITIZEN printers range contains a combination of connections through USB and ethernet simultaneously. This printer represents an investment into the future of your business, and is valuable if you do not know what tye of connecton you'll use in the future. The Printer is available in black or white colour. Printed check is dispensed from the front bottom part of the printer (as opposed to Epson printers, where checks come out on the top).

EPSON printers accessories

EPSON external buzzer for TM-T20

Alerts a user at the initialisation of the print, suitable for noisy environment such as kitchen. It is suitable for thermal printers, due to their rather quiet demeanor while printing. It connects directly to a printer.



EPSON LAN 10/100 Wthernet interface for TM series

If you already have a printer from TM series and you need to turn it into a Network printer, this is an ideal solution. Epson enables change of communication module. This module will transform RS232 printer into Ethernet printing device.



Accessories

Card/ID readers

Datalogic QuickScan STD-QW20

Reads: Bar codes (1D)

Scanner Type: CCD
Connection: USB
Stand: Yes

Standard USB reader of 1D bar codes (cannot read QR codes).

Scanner connects through USB. Offers continuous scan or scan at a press of a button. Comes with it's own stand.



Reads: magnetic cards, 3-track

Connection: USB, Directly to ELO POS terminal from the left hand side.

(USB cabel is required for installation from the right hand side)

This is original accessory for ELO POS terminals, for installation on the left hand side of the monitor frame.

Desktop magnetic card reader

Reads: Magnetic Cards

Connection: USB



This is an ideal solution for POS terminals without magnetic card scanner, suitable for scanning of client and other magnetic cards.



Cash drawer, Decibar, other

Cash drawer APG ECD 410

Robust Cash Drawer APG is supplied with cable for connection with the printer (Drawer kickback function - automatic ejection of the drawer upon print out of the bill.



USB WiFi adapter TP-Link

External USB adapter enables connection of the POS terminal to WiFi. Compatible with Windows, additional drivers are not required. Support for 802.11 b/g/n standard, up to 150 Mbps, USB2



Decibar scale

Dimensions: 190 x 210 x 95 (W x D x H) mm

Surface dimensions: 135 x 135 mm

Connection: USB



Decibar Scale measures total volume of liquid in wide variety of popular alcoholic drinks. Integration with Vento enables to convenietly measure values during stock take and import them into the Vento aplication.